VIJAY
Systems Engineers

ACE MASTIK SEALANT - A

FIRE SEALANT
Prevents the Spread of Fire
(VSPS240AS)

PRODUCT DESCRIPTION

Ace Mastik is an ablative sealant for penetration seals. Ace Mastik is applied on the perimeter of an opening and on the perimeter of mineral wool board(s) to cover small gaps.

SPECIAL FEATURES:

- It has a fire rating of up to 4 hours
- It is water - based, halogen and solvent free
- Easy to apply
- Available in cartridges for easy nozzle application
- Available in 10 & 20 kgs. pails for bulk consumption



SPECIFICATIONS

PROPERTY	PRESENT VALUE
Density	1.31 to 1.41 gms/cc
Cartridge Content	310 ml/420 gms
Storage Temperature	5°C to 50°C
Application Temperature	5°C to 50°C
Curing Time	4 to 6 hours
Ph Value	6 to 8
Color	Off-White
Odor	Odorless
Shelf Life	12 Months, In Original Packed Condition

TESTED IN ACCORDANCE WITH ASTM E 814,UL 1479 FOR 3 HRS FIRE RATING

FM APPROVED

"Subject to the conditions of Approval as a Wall Penetration Fire Stop when installed as described in the Approvals Guide, an online resource of FM Approvals"